


STANDARD SHEAVES LIST



GT
George Taylor & Co Ltd
(Founders & Engineers)

George Taylor specialises in the manufacture of Sheaves & Pulleys
Note: Details below are nominal cast sizes

Size mm	A	B	C	D
175	175	214	34	10

175mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
175-040-40-50	4.0	40	50	80	8mm
175-040-50-50	"	50	"	90	
175-040-60-50	"	60	"	100	
175-040-70-50	"	70	"	110	
175-040-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
175-045-40-50	4.5	40	50	80	9mm
175-045-50-50	"	50	"	90	
175-045-60-50	"	60	"	100	
175-045-70-50	"	70	"	110	
175-045-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
175-055-40-50	5.5	40	50	80	11mm
175-055-50-50	"	50	"	90	
175-055-60-50	"	60	"	100	
175-055-70-50	"	70	"	110	
175-055-80-50	"	80	"	120	

Size mm	A	B	C	D
225	225	273	41	10

225mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
225-045-40-50	4.5	40	50	80	9mm
225-045-50-50	"	50	"	90	
225-045-60-50	"	60	"	100	
225-045-70-50	"	70	"	110	
225-045-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
225-055-40-50	5.5	40	50	80	11mm
225-055-50-50	"	50	"	90	
225-055-60-50	"	60	"	100	
225-055-70-50	"	70	"	110	
225-055-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
225-065-40-50	6.5	40	50	80	13mm
225-065-50-50	"	50	"	90	
225-065-60-50	"	60	"	100	
225-065-70-50	"	70	"	110	
225-065-80-50	"	80	"	120	

Size mm	A	B	C	D
200	200	244	38	10

200mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
200-045-40-50	4.5	40	50	80	9mm
200-045-50-50	"	50	"	90	
200-045-60-50	"	60	"	100	
200-045-70-50	"	70	"	110	
200-045-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
200-055-40-50	5.5	40	50	80	11mm
200-055-50-50	"	50	"	90	
200-055-60-50	"	60	"	100	
200-055-70-50	"	70	"	110	
200-055-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
200-065-40-50	6.5	40	50	80	13mm
200-065-50-50	"	50	"	90	
200-065-60-50	"	60	"	100	
200-065-70-50	"	70	"	110	
200-065-80-50	"	80	"	120	

Size mm	A	B	C	D
250	250	300	43	10

250mm SERIES


Serial No.	E mm	F mm	G mm	H mm	Rope Dia
250-045-40-50	4.5	40	50	80	9mm
250-045-50-50	"	50	"	90	
250-045-60-50	"	60	"	100	
250-045-70-50	"	70	"	110	
250-045-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
250-065-40-50	6.5	40	50	80	13mm
250-065-50-50	"	50	"	90	
250-065-60-50	"	60	"	100	
250-065-70-50	"	70	"	110	
250-065-80-50	"	80	"	120	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
250-070-40-50	7.0	40	50	80	14mm
250-070-50-50	"	50	"	90	
250-070-60-50	"	60	"	100	
250-070-70-50	"	70	"	110	
250-070-80-50	"	80	"	120	



STANDARD SHEAVES LIST



George Taylor specialises in the manufacture of Sheaves & Pulleys
 Note: Details below are nominal cast sizes



George Taylor & Co Ltd
 (Founders & Engineers)

Size mm	A	B	C	D
275	333	47	10	

275mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
275-065-50-70	6.5	50	70	90	13mm
275-065-60-70	"	60	"	100	
275-065-70-70	"	70	"	110	
275-065-80-70	"	80	"	120	
275-065-90-70	"	90	"	140	
275-065-100-70	"	100	"	150	
275-065-110-70	"	110	"	160	
275-065-120-70	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
275-070-50-70	7.0	50	70	90	14mm
275-070-60-70	"	60	"	100	
275-070-70-70	"	70	"	110	
275-070-80-70	"	80	"	120	
275-070-90-70	"	90	"	140	
275-070-100-70	"	100	"	150	
275-070-110-70	"	110	"	160	
275-070-120-50	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
275-080-50-70	8.0	50	70	90	16mm
275-080-60-70	"	60	"	100	
275-080-70-70	"	70	"	110	
275-080-80-70	"	80	"	120	
275-080-90-70	"	90	"	140	
275-080-100-70	"	100	"	150	
275-080-110-70	"	110	"	160	
275-080-120-70	"	120	"	170	

Size mm	A	B	C	D
350	420	55	15	

350mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
350-080-50-75	8.0	50	75	90	16mm
350-080-60-75	"	60	"	100	
350-080-70-75	"	70	"	110	
350-080-80-75	"	80	"	120	
350-080-90-75	"	90	"	140	
350-080-100-75	"	100	"	150	
350-080-110-75	"	110	"	160	
350-080-120-75	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
350-095-50-75	9.5	50	75	90	19mm
350-095-60-75	"	60	"	100	
350-095-70-75	"	70	"	110	
350-095-80-75	"	80	"	120	
350-095-90-75	"	90	"	140	
350-095-100-75	"	100	"	150	
350-095-120-75	"	110	"	160	
350-095-130-75	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
350-110-50-75	11.0	50	75	90	22mm
350-110-60-75	"	60	"	100	
350-110-70-75	"	70	"	110	
350-110-80-75	"	80	"	120	
350-110-90-75	"	90	"	140	
350-110-100-75	"	100	"	150	
350-110-110-75	"	110	"	160	
350-110-120-75	"	120	"	170	

Size mm	A	B	C	D
300	364	50	10	

300mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
300-070-50-70	7.0	50	70	90	14mm
300-070-60-70	"	60	"	100	
300-070-70-70	"	70	"	110	
300-070-80-70	"	80	"	120	
300-070-90-70	"	90	"	140	
300-070-100-70	"	100	"	150	
300-070-110-70	"	110	"	160	
300-070-120-70	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
300-080-50-70	8.0	50	70	90	16mm
300-080-60-70	"	60	"	100	
300-080-70-70	"	70	"	110	
300-080-80-70	"	80	"	120	
300-080-90-70	"	90	"	140	
300-080-100-70	"	100	"	150	
300-080-110-70	"	110	"	160	
300-080-120-70	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
300-095-50-70	9.5	50	70	90	19mm
300-095-60-70	"	60	"	100	
300-095-70-70	"	70	"	110	
300-095-80-70	"	80	"	120	
300-095-90-70	"	90	"	140	
300-095-100-70	"	100	"	150	
300-095-110-70	"	110	"	160	
300-095-120-70	"	120	"	170	

Size mm	A	B	C	D
400	475	58	15	

400mm SERIES


Serial No.	E mm	F mm	G mm	H mm	Rope Dia
400-080-50-75	8.0	50	75	90	16mm
400-080-60-75	"	60	"	100	
400-080-70-75	"	70	"	110	
400-080-80-75	"	80	"	120	
400-080-90-75	"	90	"	140	
400-080-100-75	"	100	"	150	
400-080-110-75	"	110	"	160	
400-080-120-75	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
400-095-50-75	9.5	50	75	90	19mm
400-095-60-75	"	60	"	100	
400-095-70-75	"	70	"	110	
400-095-80-75	"	80	"	120	
400-095-90-75	"	90	"	140	
400-095-100-75	"	100	"	150	
400-095-110-75	"	110	"	160	
400-095-120-75	"	120	"	170	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
400-110-50-75	11.0	50	75	90	22mm
400-110-60-75	"	60	"	100	
400-110-70-75	"	70	"	110	
400-110-80-75	"	80	"	120	
400-110-90-75	"	90	"	140	
400-110-100-75	"	100	"	150	
400-110-110-75	"	110	"	160	
400-110-120-75	"	120	"	170	



STANDARD SHEAVES LIST



George Taylor specialises in the manufacture of Sheaves & Pulleys
 Note: Details below are nominal cast sizes



George Taylor & Co Ltd
 (Founders & Engineers)

Size mm	A	B	C	D
450	530	62	15	

450mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
450-090-70-85	9.0	70	85	120	18mm
450-090-80-85	"	80	"	130	
450-090-90-85	"	90	"	140	
450-090-100-85	"	100	"	150	
450-090-110-85	"	110	"	160	
450-090-120-85	"	120	"	180	
450-090-130-85	"	130	"	190	
450-090-140-85	"	140	"	200	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
450-110-70-85	11.0	70	85	120	22mm
450-110-80-85	"	80	"	130	
450-110-90-85	"	90	"	140	
450-110-100-85	"	100	"	150	
450-110-110-85	"	110	"	160	
450-110-120-85	"	120	"	180	
450-110-130-85	"	130	"	190	
450-110-140-85	"	140	"	200	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
450-130-70-85	13.0	70	85	120	26mm
450-130-80-85	"	80	"	130	
450-130-90-85	"	90	"	140	
450-130-100-85	"	100	"	150	
450-130-120-85	"	110	"	160	
450-130-130-85	"	120	"	180	
450-130-130-85	"	130	"	190	
450-130-140-85	"	140	"	200	

Size mm	A	B	C	D
550	640	70	20	

550mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
550-110-70-90	11.0	70	90	120	22mm
550-110-80-90	"	80	"	130	
550-110-90-90	"	90	"	140	
550-110-100-90	"	100	"	150	
550-110-110-90	"	110	"	160	
550-110-120-90	"	120	"	180	
550-110-130-90	"	130	"	190	
550-110-140-90	"	140	"	200	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
550-130-70-90	13.0	70	90	120	26mm
550-130-80-90	"	80	"	130	
550-130-90-90	"	90	"	140	
550-130-100-90	"	100	"	150	
550-130-110-90	"	110	"	160	
550-130-120-90	"	120	"	180	
550-130-130-90	"	130	"	190	
550-130-140-90	"	140	"	200	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
550-140-70-90	14.0	70	90	120	28mm
550-140-80-90	"	80	"	130	
550-140-90-90	"	90	"	140	
550-140-100-90	"	100	"	150	
550-140-110-90	"	110	"	160	
550-140-120-90	"	120	"	180	
550-140-130-90	"	130	"	190	
550-140-140-90	"	140	"	200	

Size mm	A	B	C	D
500	585	66	15	

500mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
500-100-70-85	10.0	70	85	120	20mm
500-100-80-85	"	80	"	130	
500-100-90-85	"	90	"	140	
500-100-100-85	"	100	"	150	
500-100-110-85	"	110	"	160	
500-100-120-85	"	120	"	180	
500-100-130-85	"	130	"	190	
500-100-140-85	"	140	"	200	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
500-110-70-85	11.0	70	85	120	22mm
500-110-80-85	"	80	"	130	
500-110-90-85	"	90	"	140	
500-110-100-85	"	100	"	150	
500-110-110-85	"	110	"	160	
500-110-120-85	"	120	"	180	
500-110-130-85	"	130	"	190	
500-110-140-85	"	140	"	200	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
500-140-70-85	14.0	70	85	120	28mm
500-140-80-85	"	80	"	130	
500-140-90-85	"	90	"	140	
500-140-100-85	"	100	"	150	
500-140-110-85	"	110	"	160	
500-140-120-85	"	120	"	180	
500-140-130-85	"	130	"	190	
500-140-140-85	"	140	"	200	

Size mm	A	B	C	D
600	695	75	20	

600mm SERIES


Serial No.	E mm	F mm	G mm	H mm	Rope Dia
600-120-80-90	12.0	80	90	130	24mm
600-120-90-90	"	90	"	140	
600-120-100-90	"	100	"	150	
600-120-110-90	"	110	"	160	
600-120-120-90	"	120	"	180	
600-120-130-90	"	130	"	190	
600-120-140-90	"	140	"	200	
600-120-150-90	"	150	"	210	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
600-130-80-90	13.0	80	90	130	26mm
600-130-90-90	"	90	"	140	
600-130-100-90	"	100	"	150	
600-130-110-90	"	110	"	160	
600-130-120-90	"	120	"	180	
600-130-130-90	"	130	"	190	
600-130-140-90	"	140	"	200	
600-130-150-90	"	150	"	210	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
600-160-80-90	16.0	80	90	130	32mm
600-160-90-90	"	90	"	140	
600-160-100-90	"	100	"	150	
600-160-110-90	"	110	"	160	
600-160-120-90	"	120	"	180	
600-160-130-90	"	130	"	190	
600-160-140-90	"	140	"	200	
600-160-150-90	"	150	"	210	



STANDARD SHEAVES LIST



George Taylor specialises in the manufacture of Sheaves & Pulleys
 Note: Details below are nominal cast sizes



George Taylor & Co Ltd
 (Founders & Engineers)

Size mm	A	B	C	D
650	750	80	20	

650mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
650-120-80-90	12.0	80	90	130	24mm
650-120-90-90	"	90	"	140	
650-120-100-90	"	100	"	150	
650-120-110-90	"	110	"	160	
650-120-120-90	"	120	"	180	
650-120-130-90	"	130	"	190	
650-120-140-90	"	140	"	200	
650-120-150-90	"	150	"	210	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
650-140-80-90	14.0	80	90	130	28mm
650-140-90-90	"	90	"	140	
650-140-100-90	"	100	"	150	
650-140-110-90	"	110	"	160	
650-140-120-90	"	120	"	180	
650-140-130-90	"	130	"	190	
650-140-140-90	"	140	"	200	
650-140-150-90	"	150	"	210	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
650-175-80-90	17.5	80	90	130	35mm
650-175-90-90	"	90	"	140	
650-175-100-90	"	100	"	150	
650-175-110-90	"	110	"	160	
650-175-120-90	"	120	"	180	
650-175-130-90	"	130	"	190	
650-175-140-90	"	140	"	200	
650-175-150-90	"	150	"	210	

Size mm	A	B	C	D
750	860	85	25	

750mm SERIES

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
750-130-80-95	13.0	80	95	130	26mm
750-130-90-95	"	90	"	140	
750-130-100-95	"	100	"	150	
750-130-110-95	"	110	"	160	
750-130-120-95	"	120	"	180	
750-130-130-95	"	130	"	190	
750-130-140-95	"	140	"	200	
750-130-150-95	"	150	"	210	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
750-160-80-95	16.0	80	95	130	32mm
750-160-90-95	"	90	"	140	
750-160-100-95	"	100	"	150	
750-160-110-95	"	110	"	160	
750-160-120-95	"	120	"	180	
750-160-130-95	"	130	"	190	
750-160-140-95	"	140	"	200	
750-160-150-95	"	150	"	210	

Serial No.	E mm	F mm	G mm	H mm	Rope Dia
750-190-80-95	19.0	80	95	130	38mm
750-190-90-95	"	90	"	140	
750-190-100-95	"	100	"	150	
750-190-110-95	"	110	"	160	
750-190-120-95	"	120	"	180	
750-190-130-95	"	130	"	190	
750-190-140-95	"	140	"	200	
750-190-150-95	"	150	"	210	

